

Gama Comercial Suelo-Techo		AVT52UR4RSA4	AUV71UR4RFA4	AUV90UR4RFB4	
Unidad interior		AVT52UR4RA4	AUV71UR4RA4	AUV90UR4RB4	
Unidad exterior		AUW52U4RS4	AUW71U4RF4	AUW90U4RF4	
Capacidad	Frío Nominal (Mín-Máx)	Frig/h	4558(1625-4747)	6192(1368-7629)	7568 (3010-8170)
	Frío Nominal (Mín-Máx)	kW	5300 (1890-5520)	7200 (1591-8871)	8800 (3500~9500)
	Calor Nominal (Mín-Máx)	Kcal/h	4988 (1410-5168)	6794 (1503-8158)	7740 (3440-8772)
	Calor Nominal (Mín-Máx)	kW	5800(1640-6010)	7900 (1748-9487)	9000 (4000~10200)
Consumo Nominal					
	SEER (Rango)		6,33	6,11	6,1
	SCOP (Rango)*		4,41	4,18	4,1
Clasificación Energética	Frío	Frig/h	A++	A++	A++
	Calor	Kcal/h	A+	A+	A+
Unidad Interior	Caudal de aire (A/M/B)	m <sup>3</sup> /min	800/690/590	1100/950/800	1500/1400/1150
	Nivel sonoro (A/M/B)	dB(A)	41/37/34	51/48/45	52/51/49
	Potencia sonora	dB(A)	57	63	64
	Dimensiones An x Al x Fon	mm	990x230x680	990x230x680	1285x230x680
	Peso Neto/con embalaje	kg	34/38.5	51/57	51/57
Unidad Exterior					
	Nivel sonoro (A)	dB(A)	54	53	55
	Potencia sonora	dB(A)	65	68	69
	Dimensiones An x Alx Fon	mm	810x585x280	860x670x310	860x670x310
	Peso Neto/con embalaje	kg	29/34	30/35	37/44
Refrigerante	Gas		R32	R32	R32
	Carga Kg		0,97	1,4	1,45
Diám. tuberías líquido/gas		mm/pulg	Φ6.35/Φ12.7(1/4"/1/2')	Φ9.52/Φ15.88(3/8"/5/8')	Φ9.52/Φ15.88(3/8"/5/8')
Long. Máx. tubería total/vert		m	30/15	50/30	50/30
Rango de operación	Tª ext. refrigeración	°C	-15~48	-15~48	-15~48
	Tª ext. calefacción	°C	-15~24	-15~24	-15~24
Gama Comercial Suelo-Techo		AUV105UR4RAB4	AUV125UR6RTC4	AUV140UR6RPC4	AUV175UR6RPC4
Unidad interior		AUV105UR4RB4	AUV125UR4RC4	AUV140UR4RC4	AUV175UR4RC4
Unidad exterior		AUW105U4RA4	AUW125U6RT4	AUW140U6RP4	AUW175U6RP4
Frío Nominal (Mín-Máx)	Frig/h	9030 (3010-9460)	10750 (1376-11094)	12384 (2211-11833)	15050 (3682-15910)
Frío Nominal (Mín-Máx)	kW	10500(3500-11000)	12500 (1600-12900)	14400 (3200~16000)	17500 (3300~18500)
Calor Nominal (Mín-Máx)	Kcal/h	9890 (2855-10320)	11524 (3182-13330)	14878(2924-15910)	15910 (2580-16770)
Calor Nominal (Mín-Máx)	kW	11500 (3320-12000)	13400 (3700-15500)	17300 (3400~18500)	18500 (3000~19500)
Consumo Nominal					
	SEER (Rango)		6,1	---	---
	SCOP (Rango)*		4	---	---
Frío	Frig/h		A++	---	---
Calor	Kcal/h		A+	---	---
Caudal de aire (A/M/B)	m <sup>3</sup> /min	1700/1500/1300	2000/1800/1600	2000/1600/1200	2000/1700/1500
Nivel sonoro (A/M/B)	dB(A)	50/49/47	53/50/47	53/48/42	53/50/47
Potencia sonora	dB(A)	65	66	68	67
Dimensiones An x Al x Fon	mm	1285x230x680	1580x230x680	1580x230x680	1580x230x680
Peso Neto/con embalaje	kg	70/80	85/95	101.5/114.5	117/129
Unidad Exterior					
	Nivel sonoro (A)	dB(A)	57	58	59
	Potencia sonora	dB(A)	70	74	74
	Dimensiones An x Alx Fon	mm	950x840x340	950x1050x340	950x1386x340
	Peso Neto/con embalaje	kg	37/44	48/56	48/56
Refrigerante	Gas		R32	R32	R32
	Carga Kg		2	2,5	3
Diám. tuberías líquido/gas		mm/pulg	Φ9.52/Φ19.05(3/8"/3/4')	Φ9.52/Φ19.05(3/8"/3/4')	Φ9.52/Φ19.05(3/8"/3/4')
Long. Máx. tubería total/vert		m	50/30	50/30	50/30
Tª ext. refrigeración	°C		-15~48	-15~48	-15~48
Tª ext. calefacción	°C		-15~24	-15~24	-15~24